


ROGGA

147-0204501240496650

ROGGA M PD VOLARE SUSPENSION WITH 2-PH VOLARE ADAPTER made of aluminium, black, similar to RAL 9005, decor black, high-efficiently vacuum deposited aluminium reflector beam 50°, light output direct, with converter, max. 300mA, dimmability: not dimmable, cable black, adapter/ceiling base black, pendant length 1500mm, IP20




DRAWING



TECHNICAL DETAILS

System perform. [W]	6,5
Bulb type	LED
Luminous flux [lm]	620
Current sec. [mA]	300
Colour temp. [K]	3000K
CRI	PREMIUM>90
Optics	vacuum deposited aluminium reflector
Designer	INHOUSE
Converter	with converter
Dimming	not dimmable
Light output	direct
Beam angle [°]	50°
Voltage [V]	220-240V 50/60Hz
Material	aluminium
Length [mm]	320
Pendant length [mm]	1500
Diameter [mm]	41
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	0,80
Colour lamp	black
RAL	9005
Colour adapter/ceiling base	black
Colour decor	black
Electric wire	black
EAN-Number	9010870831391
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	D
No. of luminaires B16A	127

LIGHT DISTRIBUTION CURVE



energy label



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.