


**VARIDO 2**

**149-00102021905p**

VARIDO 2 DARK TRACK SPOTLIGHT WITH 3 PH ADAPTER made of steel sheet, white, similar to RAL 9016, Lens optics with vacuum deposited Dark reflector beam 66°, light output direct, UGR <19, swiveling 350°, with converter, max. 850mA, dimmability: Pulse-DALI, adapter/ceiling base white, IP20




**DRAWING**



**TECHNICAL DETAILS**

System perform. [W]	32
Bulb type	LED
Luminous flux [lm]	3860
Current sec. [mA]	850
Colour temp. [K]	3000K
CRI	>80
UGR	<19
Optics	Lens optics with vacuum deposited Dark reflector
Designer	INHOUSE
Converter	with converter
Light output	direct
Beam angle [°]	66°
Voltage [V]	220-240V 50/60Hz
Material	steel sheet
Length [mm]	844
Width [mm]	54
Height [mm]	24
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	1,54
Colour lamp	white
RAL	9016
Colour adapter/ceiling base	white
EAN-Number	9010506112016
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	C
No. of luminaires B16A	50

**LIGHT DISTRIBUTION CURVE**



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.