


30NE

175-0265052231440

30NE SKII DIFFUSER LUMINAIRE made of glass fibre reinforced polyester, grey, similar to RAL 7035, polycarbonate cover light output direct, with converter, dimmability: not dimmable, IP66




DRAWING



TECHNICAL DETAILS

System perform. [W]	38
Bulb type	LED
Luminous flux [lm]	5200
Colour temp. [K]	4000K
CRI	>80
Optics	polycarbonate cover
Converter	with converter
Dimming	not dimmable
Light output	direct
Voltage [V]	220-240V 50/60Hz
Material	glass fibre reinforced polyester
Length [mm]	1577
Width [mm]	90
Height [mm]	95
IP protection class	IP66
Voltage class	protection cl. II
Shock resistance	IK08
Net weight [kg]	2,08
Colour lamp	grey
RAL	7035
EAN-Number	9010506635676
Lifetime [h]	50 000 L80 B10
Energy efficiency cl.	D
No. of luminaires B16A	35
IFS suitable	Yes

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.