LORA

176-1020500023660

LORA 5 PD SUSPENSION made of steel, black, similar to RAL 7016, white black, beam 42°, light output direct, with converter, max. 500mA, dimmability: not dimmable, cable black, adapter/ceiling base black, pendant length 1500mm, IP20

DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	10
Bulb type	LED
Luminous flux [lm]	690
Current sec. [mA]	500
Colour temp. [K]	2700K
CRI	>90
Converter	with converter
Dimming	not dimmable
Light output	direct
Beam angle [°]	42°
Voltage [V]	220-240V 50/60Hz
Material	steel
Length [mm]	330
Height [mm]	100
Pendant length [mm]	1500
Diameter [mm]	360
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	1,53
Colour lamp	black
RAL	7016
Colour of glass/shade	white black
Colour adapter/ceiling base	black
Electric wire	black
EAN-Number	9010506764475
Lifetime [h]	L80 B10 20 000
Energy efficiency cl.	E

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.