DIVO SHORT

192-202020002355d

DIVO SHORT PD SUSPENSION made of aluminium, white, similar to RAL 9003,high quality plastic lens beam 36°, light output direct, with converter, max. 250mA, dimmability: DALI, cable white, adapter/ceiling base white, pendant length 3000mm, IP20

DRAWING



TECHNICAL DETAILS

System perform. [W]	11
Bulb type	LED
Luminous flux [lm]	680
Current sec. [mA]	250
Colour temp. [K]	2700K
CRI	>90
Optics	high quality plastic lens
Converter	with converter
Light output	direct
Beam angle [°]	36°
Voltage [V]	220-240V 50/60Hz
Material	aluminium
Length [mm]	300
Pendant length [mm]	3000
Diameter [mm]	57
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	1,30
Colour lamp	white
RAL	9003
Colour adapter/ceiling base	white
Electric wire	white
EAN-Number	9010506764024
Lifetime [h]	L80 B10 20 000
Energy efficiency cl.	F

LIGHT DISTRIBUTION CURVE



CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.