MOLTO LUCE®

DIVO SHORT

192-209020002964b

DIVO SHORT VOLARE SUSPENSION WITH 2-PH VOLARE ADAPTER made of aluminium, black, similar to RAL 9005,high quality plastic lens beam 36°, light output direct, with converter, max. 260mA, dimmability: Smart bluetooth, cable black, adapter/ceiling base silver, pendant length 3000mm, IP20

DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	12
Bulb type	LED
Luminous flux [lm]	680
Current sec. [mA]	260
Colour temp. [K]	3000K
CRI	>90
Optics	high quality plastic lens
Converter	with converter
Light output	direct
Beam angle [°]	36°
Voltage [V]	220-240V 50/60Hz
Material	aluminium
Length [mm]	300
Pendant length [mm]	3000
Diameter [mm]	57
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	1,17
Colour lamp	black
RAL	9005
Colour adapter/ceiling base	silver
Electric wire	black
EAN-Number	9010506772975
Lifetime [h]	L80 B10 20 000
Energy efficiency cl.	G

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.