

## KONVERTER KONST. STROM

24-122203

multipower driver, not dimm.; 100mA 5,4W / 140mA 7,7W / 180mA 9,9W / 220mA 12W /  
260mA 14,3W / 300mA 16,5W / 340mA 18,6W / 380mA 20W  
24V DC 9W (380mA max.)  
ceiling cut out =55mm



## DRAWING

## TECHNICAL DETAILS

Dimming	not dimmable
Voltage [V]	220-240V 50/60Hz
Material	synthetic
Length [mm]	111
Width [mm]	52
Height [mm]	22
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	0,08
Colour lamp	white
EAN-Number	8010703310971
No. of luminaires B16A	50

## LIGHT DISTRIBUTION CURVE

DIP-SWITCH Einstellungen: 24-122203		
P out W	V out DC	I out DC
5,4W	20 ... 54	100mA Konstantstrom
7,5W	10 ... 54	140mA Konstantstrom
10W	2 ... 54	180mA Konstantstrom
12W	2 ... 54	220mA Konstantstrom
14W	2 ... 54	260mA Konstantstrom
16W	2 ... 54	300mA Konstantstrom
18W	2 ... 54	340mA Konstantstrom
20W	2 ... 54	380mA Konstantstrom
9W	24	Max. 380mA Konstantspannung



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.