

KONVERTER DIMMBAR KONST. STROM

24-151504



DRAWING

TECHNICAL DETAILS

System perform. [W]	18,5-50
Converter	with converter
Voltage [V]	220-240V 50/60Hz
Material	synthetic
Length [mm]	124
Width [mm]	79
Height [mm]	22
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	0,21
Colour lamp	white
EAN-Number	8010703385290
No. of luminaires B16A	30

LIGHT DISTRIBUTION CURVE

DIP-SWITCH Einstellungen: 24-151504		
P out W	V out DC	I out DC
18,5W	10 ... 53	350mA Konstantstrom
21W	10 ... 53	400mA Konstantstrom
23,5W	10 ... 53	450mA Konstantstrom
26,5W	10 ... 53	500mA Konstantstrom
29W	10 ... 53	550mA Konstantstrom
31,5W	10 ... 53	600mA Konstantstrom
34,5W	10 ... 53	650mA Konstantstrom
37W	10 ... 53	700mA Konstantstrom
39,5W	10 ... 53	750mA Konstantstrom
42W	10 ... 53	800mA Konstantstrom
45W	10 ... 53	850mA Konstantstrom
47,5W	10 ... 53	900mA Konstantstrom
50W	10 ... 52	950mA Konstantstrom
50W	10 ... 50	1A Konstantstrom
50W	10 ... 48	1,05A Konstantstrom
50W	10 ... 45	1,1A Konstantstrom
50W	10 ... 43	1,15A Konstantstrom
50W	10 ... 41	1,2A Konstantstrom



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.