

GILO

472-2429160

GILO PD SUSPENSION made of aluminium, black matt, similar to RAL 9005, satined, light output direct, with converter, dimmable not dimmable, cable coax transparent, adapter/ceiling base black matt, pendant length 2000mm, IP20



DRAWING

TECHNICAL DETAILS

| | |
|---------------------|------------------|
| System perform. [W] | 7 |
| Bulb type | LED |
| Luminous flux [lm] | 338 |
| Colour temp. [K] | 3000K |
| CRI | >90 |
| Converter | with converter |
| Dimming | not dimmable |
| Light output | direct |
| Voltage [V] | 220-240V 50/60Hz |
| Material | aluminium |

| | |
|---------------------|------------------|
| Height [mm] | 90 |
| Pendant length [mm] | 2000 |
| Diameter [mm] | 80 |
| IP protection class | IP20 |
| Voltage class | protection cl. I |
| Net weight [kg] | 0,75 |

LIGHT DISTRIBUTION CURVE

| | |
|----------------------------|--------------------------------|
| Color lamp | black matt |
| RAL | 9005 |
| Glass color | satined |
| Color adapter/ceiling base | black matt coax transparent |
| Electric wire | 9010506027167 |
| EAN-Number | 25 000 |
| Lifetime [h] | |



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.