


DARK NIGHT XS

527-0009020443050

DARK NIGHT TURN XS SD SURFACE MOUNTED DOWNLIGHT made of aluminium, white, similar to RAL 9016, decor silver, high-efficiently vacuum deposited aluminium reflector beam 60°, light output direct, UGR <19, swiveling 355°, tilting 25°, with converter, max. 250mA, dimmability: not dimmable, IP20




DRAWING



TECHNICAL DETAILS

System perform. [W]	9
Bulb type	LED
Luminous flux [lm]	600
Current sec. [mA]	250
Colour temp. [K]	2700K
CRI	PREMIUM>90
UGR	<19
Optics	vacuum deposited aluminium reflector
Converter	with converter
Dimming	not dimmable
Light output	direct
Beam angle [°]	60°
Voltage [V]	220-240V 50/60Hz
Material	aluminium
Height [mm]	115
Diameter [mm]	85
IP protection class	IP20
Voltage class	protection cl. I
Shock resistance	IK02
Net weight [kg]	0,67
Colour lamp	white
RAL	9016
Colour decor	silver
EAN-Number	9010506860955
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	D
No. of luminaires B16A	50

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.