MOLTO LUCE®

VOLTO COPERTO

539-010011024060

VOLTO COPERTO SD WALL / CEILING LUMINAIRE made of die-cast aluminium, black anodised, similar to RAL 9005, satined PMMA diffuser for homogeneous illumination satined, light output direct, with converter, dimmability: not dimmable, IP20

DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	11
Bulb type	LED
Luminous flux [lm]	810
Colour temp. [K]	4000K
CRI	>90
Optics	PMMA opal diffuser flat
Designer	INHOUSE
Converter	with converter
Dimming	not dimmable
Light output	direct
Voltage [V]	220-240V 50/60Hz
Material	die-cast aluminium
Width [mm]	26
Height [mm]	39
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	0,97
Colour lamp	black anodised
RAL	9005
Colour of glass/shade	satined
EAN-Number	9008905686535
Lifetime [h]	L80 B10 50 000

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.