


LITIN 2.0

540-04123131b6060


LITIN 2 PD SUSPENSION made of aluminium, black, similar to RAL 9005, decor copper, high quality plastic lens beam 40°, light output direct, dimmability: not dimmable, cable black, adapter/ceiling base black, pendant length 3000mm, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

| | |
|-----------------------------|---------------------------|
| System perform. [W] | 10 |
| Bulb type | LED |
| Luminous flux [lm] | 720 |
| Colour temp. [K] | 2700K |
| CRI | >90 |
| Optics | high quality plastic lens |
| Designer | INHOUSE |
| Dimming | not dimmable |
| Light output | direct |
| Beam angle [°] | 40° |
| Voltage [V] | 220-240V 50/60Hz |
| Material | aluminium |
| Height [mm] | 114 |
| Pendant length [mm] | 3000 |
| Diameter [mm] | 90 |
| IP protection class | IP20 |
| Voltage class | protection cl. II |
| Net weight [kg] | 1,19 |
| Colour lamp | black |
| RAL | 9005 |
| Colour adapter/ceiling base | black |
| Colour decor | copper |
| Electric wire | black |
| EAN-Number | 9010506830811 |
| Lifetime [h] | 30 000 |
| Energy efficiency cl. | G |



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.