


LITIN 2.0

540-05110131d6060


LITIN 2 VOLARE TRACK SPOTLIGHT WITH 2 PH VOLARE ADAPTER made of aluminium, black, similar to RAL 9005, decor gold, satined PMMA opal diffuser beam 105°, light output direct, swiveling 350°, tilting 90°, dimmability: not dimmable, adapter/ceiling base black, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	10
Bulb type	LED
Luminous flux [lm]	530
Colour temp. [K]	2700K
CRI	>90
Optics	PMMA opal diffuser
Designer	INHOUSE
Dimming	not dimmable
Light output	direct
Beam angle [°]	105°
Voltage [V]	220-240V 50/60Hz
Material	aluminium
Length [mm]	92,6
Height [mm]	140
Diameter [mm]	90
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	0,77
Colour lamp	black
RAL	9005
Colour adapter/ceiling base	black
Colour decor	gold
EAN-Number	9010506778410
Lifetime [h]	30 000
Energy efficiency cl.	G



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.