

RIDE

577-01303202305d

RIDE IP54 SD SURFACE MOUNTED CEILING LUMINAIRE made of die-cast aluminium, white, similar to RAL 9016,satined PMMA diffuser cubic for homogeneous illumination light output direct, with converter, max. 500mA, dimmability: DALI, IP54

DRAWING

TECHNICAL DETAILS

System perform. [W]	19
Bulb type	LED
Luminous flux [lm]	1650
Current sec. [mA]	500
Colour temp. [K]	2700K
CRI	>90
Optics	PMMA opal diffuser cubic
Designer	INH0USE
Converter	with converter
Light output	direct
Voltage [V]	220-240V 50/60Hz
Material	die-cast aluminium
Length [mm]	1138,2
Width [mm]	39
Height [mm]	72
IP protection class	IP54
Voltage class	protection cl. I
Shock resistance	IK03
Net weight [kg]	2,21
Colour lamp	white
RAL	9016
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	E
No. of luminaires B16A	50

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.