


AFTER 8

601-01041102305d

AFTER 8 PDI SUSPENSION made of aluminium, white, similar to RAL 9016, sated PMMA opal diffuser light output direct / indirect 60:40, with converter, max. 1050mA, dimmable DALI, cable Tension control in the suspension ropes, adapter/ceiling base white, pendant length 2000mm, IP20



DRAWING




TECHNICAL DETAILS

System perform. [W]	41
Bulb type	LED
Luminous flux [lm]	1900
Current sec. [mA]	1050
Colour temp. [K]	2700K
CRI	>90
Optics	PMMA opal diffuser
Designer	INHOUSE
Converter	with converter
Dimming	DALI
Light output	direct / indirect 60:40
Voltage [V]	220-240V 50/60Hz
Material	aluminium

Width [mm]	5
Height [mm]	80
Pendant length [mm]	2000
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	4,49

LIGHT DISTRIBUTION CURVE



Color lamp	white
RAL	9016
Color adapter/ceiling base	white
	Tension control in the suspension ropes
Electric wire	9008905928024
EAN-Number	L80 B10 50 000
Lifetime [h]	24
No. of luminaires B16A	



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.