


AFTER 8

601-01041102405z


AFTER 8 PDI SUSPENSION made of aluminium, white, similar to RAL 9016, sated PMMA opal diffuser light output direct / indirect 60:40, with converter, max. 1050mA, dimmable Zigbee 3.0, cable Tension control in the suspension ropes, adapter/ceiling base white, pendant length 2000mm, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	41
Bulb type	LED
Luminous flux [lm]	2070
Current sec. [mA]	1050
Colour temp. [K]	4000K
CRI	>90
Optics	PMMA opal diffuser
Designer	INHOUSE
Converter	with converter
Dimming	Zigbee 3.0
Light output	direct / indirect 60:40
Voltage [V]	220-240V 50/60Hz
Material	aluminium
Width [mm]	5
Height [mm]	80
Pendant length [mm]	2000
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	4,49
Color lamp	white
RAL	9016
Color adapter/ceiling base	white
Electric wire	Tension control in the suspension ropes
EAN-Number	9008905928420
Lifetime [h]	L80 B10 50 000



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.