


TRAIL

610-130003164955d

TRAIL MOVA M MOUNTING RAIL LIGHT INSERT made of aluminium, white, similar to RAL 9016, decor white, high-efficiently vacuum deposited aluminium reflector without safety glass beam 60°, light output direct, swiveling 350°, tilting 90°, with converter, max. 700mA, dimmability: DALI, through wiring 7-polig, adapter/ceiling base white, IP20




DRAWING



TECHNICAL DETAILS

System perform. [W]	27
Bulb type	LED
Luminous flux [lm]	2940
Current sec. [mA]	700
Colour temp. [K]	3000K
CRI	PREMIUM>90
Optics	aluminium reflector without protection glass
Designer	INHOUSE
Converter	with converter
Light output	direct
Beam angle [°]	60°
Voltage [V]	220-240V 50/60Hz
Through wiring	7-polig
Material	aluminium
Length [mm]	564,9
Height [mm]	156
Diameter [mm]	82
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	0,96
Colour lamp	white
RAL	9016
Colour adapter/ceiling base	white
Colour decor	white
EAN-Number	9010870131972
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	E
No. of luminaires B16A	50

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.