


DASH L DC

676-002010143660v1


DASH L DC 2 TRACK TRACK SPOTLIGHT WITH 3 PH ADAPTER made of aluminium, black matt, similar to RAL 9005,high-efficiently vacuum deposited aluminium reflector beam 20°, light output direct, swiveling 350°, tilting 90°, with converter, max. 650mA, dimmable not dimmable, adapter/ceiling base black matt, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	25
Bulb type	LED
Luminous flux [lm]	1240
Current sec. [mA]	650
Colour temp. [K]	2700K
CRI	PREMIUM>90
Optics	vacuum deposited aluminium reflector
Designer	INHOUSE
Converter	with converter
Dimming	nicht dimmbar
Light output	direct
Beam angle [°]	20°
Voltage [V]	220-240V 50/60Hz
Material	aluminium
Length [mm]	175
Height [mm]	125
Diameter [mm]	65
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	1,05
Color lamp	black matt
RAL	9005
Color adapter/ceiling base	black matt
	9010506122671
EAN-Number	L80 B10 50 000
Lifetime [h]	50
No. of luminaires B16A	



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.