


DARK NIGHT XS 684-00302054705


DARK NIGHT XS R RECESSED SPOTLIGHT made of aluminium, white matt, similar to RAL 9016, decor silver, high-efficiently vacuum deposited aluminium reflector beam 40°, light output direct, UGR <19, without converter, max. 250/350mA, dimmability: see converter, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

 Bulb type
 LED 9/13W

 Luminous flux [lm]
 810/1090

 Current sec. [mA]
 250/350

 Colour temp. [K]
 3500K

 CRI
 PREMIUM>90

 UGR
 <19</td>

<19 cs vacuum deposited aluminium reflector

Optics vacuum deposited
Designer INHOUSE
Converter without converter
Dimming see converter
Light output direct
Beam angle [°] 40°
Material aluminium

Height [mm] 78 65 Diameter [mm] Ceiling cutout [mm] 60 Ceiling thickness [mm] 1-25 Recess depth [mm] 108 IP protection class Voltage class IP20 protection cl. II Shock resistance K02 Net weight [kg] 0,21

Colour lamp white matt RAL 9016 Colour decor silver

EAN-Number 9010506051261 Lifetime [h] L80 B10 50 000

 ϵ

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.