
DARK NIGHT XS

684-00303054706


DARK NIGHT XS R RECESSED SPOTLIGHT made of aluminium, black, similar to RAL 9005, decor black, high-efficiently vacuum deposited aluminium reflector beam 40°, light output direct, UGR <19, without converter, max. 250/350mA, dimmability: see converter, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

Bulb type Luminous flux [lm] Current sec. [mA] Colour temp. [K] CRI UGR Optics Designer Converter Dimming Light output Beam angle [°] Material

Length [mm] Height [mm] Diameter [mm] Ceiling cutout [mm] Ceiling thickness [mm] Recess depth [mm] IP protection class Voltage class Shock resistance Net weight [kg]

Colour lamp RAL Colour decor EAN-Number Lifetime [h] LED 9/13W 810/1090 250/350 3500K PREMIUM>90 <19 vacuum deposited aluminium reflector INHOUSE without converter see converter direct 40° aluminium 65

78 65 60 1-25 108 IP20 protection cl. II IK02 0,34

black 9005 black 9010506051292 L80 B10 50 000

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.