


DARK NIGHT XS

684-00702054346b


DARK NIGHT XS VOLARE SUSPENSION WITH 2-PH VOLARE ADAPTER made of aluminium, black matt, similar to RAL 9005, decor silver, high-efficiently vacuum deposited aluminium reflector beam 40°, light output direct, UGR <19, with converter, max. 400mA, dimmability: Smart bluetooth, cable black, adapter/ceiling base grey, pendant length 3000mm, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W] 16 Bulb type Luminous flux [lm] LED 1160 Current sec. [mA] 400 Colour temp. [K] CRI UGR <19 Optics Designer Converter Light output Beam angle [°] direct 40° Voltage [V] Material 120 Height [mm] Pendant length [mm] Diameter [mm] 60 IP protection class IP20 Voltage class Net weight [kg] Colour lamp RAL Colour adapter/ceiling base Colour decor Electric wire EAN-Number Lifetime [h] Energy efficiency cl.

LD LED 1160 400 2700K PREMIUM>90 <19 vacuum deposited aluminium reflector INHOUSE with converter direct 40° 220-240V 50/60Hz aluminium

120 3000 60 IP20 protection cl. II 0,68

black matt 9005 grey silver black 9010506290264 L80 B10 50 000 E

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.