LOG 50 SYSTEM

715-07131a044305d

LOG 50 MAGNETICS EINSATZ LIGHT INSERT made of aluminium, white, similar to RAL 9016,high-efficiently vacuum deposited synthetic reflector beam 38°, light output direct, swiveling 350°, tilting 90°, with converter, max. 250mA, dimmability: DALI, through wiring 3x1,5mm² + 2x1,0mm², IP20

DRAWING



LIGHT DISTRIBUTION CURVE

TECHNICAL DETAILS

System perform. [W]	11
Bulb type	LED
Luminous flux [lm]	730
Current sec. [mA]	250
Colour temp. [K]	2700K
CRI	PREMIUM>90
Optics	vacuum deposited synthetic reflector
Designer	INHOUSE
Converter	with converter
Light output	direct
Beam angle [°]	38°
Voltage [V]	220-240V 50/60Hz
Through wiring	3x1,5mm² + 2x1,0mm²
Material	aluminium
Length [mm]	280
Width [mm]	49
Height [mm]	66
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	0,45
Colour lamp	white
RAL	9016
EAN-Number	9010506408966
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	E
No. of luminaires B16A	50

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.