
CONCEPT

723-10111011455m


CONCEPT LEFT F FLOOR LAMP made of aluminium, white, similar to RAL 9016,microfaceted free-form reflector beam for single workplace, light output direct / indirect 30:70, UGR <19, with converter, max. 1500mA, dimmability: motion swarm, with motion detector, day light control and swarm function, cable black, IP20 out of the box mode - with activated daylight control and motion detection







LIGHT DISTRIBUTION CURVE





TECHNICAL DETAILS

System perform. [W]
Bulb type
Luminous flux [lm]
Current sec. [mA]
Colour temp. [K]
CRI
UGR
Optics
Designer
Converter
Dimming
Motion detector
Light output
Beam angle [°]
Voltage (V)
Material
Length (mm)
Width [mm]
Height (mm)
IP protection class
Voltage class
Net weight [kg]
0 0

Colour lamp RAL Electric wire EAN-Number Lifetime [h] Energy efficiency cl. No. of luminaires B16A 7710 1500 4000K >80 <19 microfaceted free-form reflector INHOUSE with converter motion swarm with motion detector, day light control and swarm function direct / indirect 30:70 für Einzelarbeitsplatz 220-240V AC/DC aluminium

355 131 2077 IP20 protection cl. I 12,32

70 LED

white 9016 black 9010506849356 L80 B10 50 000 D 18

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.