


CONCEPT 723-10111011955m


CONCEPT LEFT F FLOOR LAMP made of aluminium, white, similar to RAL 9016, microfaceted free-form reflector beam for single workplace, light output direct / indirect 30:70, UGR <19, with converter, max. 1500mA, dimmability: motion swarm, with motion detector, day light control and swarm function, cable black, IP20 out of the box mode - with activated daylight control and motion detection



DRAWING



LIGHT DISTRIBUTION CURVE





TECHNICAL DETAILS

70 LED System perform. [W] Bulb type Luminous flux [lm] 7400 Current sec. [mA] 1500 Colour temp. [K] 3000K CRI >80 UGR <19

Optics microfaceted free-form reflector

Designer INHOUSE Converter with converter Dimming Motion detector

motion swarm with motion detector, day light control and swarm function

direct / indirect 30:70 Light output Beam angle [°] für Einzelarbeitsplatz Voltage [V] 220-240V AC/DC Material aluminium

Length [mm] Width [mm] 131 Height [mm] 2077 IP protection class IP20

protection cl. I Voltage class Net weight [kg] 12,32

Colour lamp RAL white 9016 Electric wire black

9010506849370 EAN-Number Lifetime [h] L80 B10 50 000

18

Energy efficiency cl. No. of luminaires B16A

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.