LOG 2.1. SYSTEM

728-602041114050

LOG 2.1 SYSTEM EINSATZ BINA OPAL LIGHT INSERT made of aluminium, white, similar to RAL 9016,satined PMMA opal diffuser light output direct, with converter, max. 450mA, dimmability: not dimmable, through wiring 3x1,5mm², IP20

DRAWING



LIGHT DISTRIBUTION CURVE

TECHNICAL DETAILS

System perform. [W]	16
Bulb type	LED
Luminous flux [lm]	2140
Current sec. [mA]	450
Colour temp. [K]	4000K
CRI	>80
Optics	PMMA opal diffuser
Designer	INHOUSE
Converter	with converter
Dimming	not dimmable
Light output	direct
Voltage [V]	220-240V 50/60Hz
Through wiring	3x1,5mm²
Material	aluminium
Length [mm]	1124
IP protection class	IP20
Voltage class	protection cl. I
Shock resistance	IK06
Net weight [kg]	2,26
Colour lamp	white
RAL	9016
EAN-Number	9010506090369
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	D
No. of luminaires B16A	50

CE

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.