

BASIC

746-1249167rgbw

Flexible BASIC LED Stripe RGB-W, roll 5000mm, 240 RGB 5050 LEDs, 240 white 2835 LEDs, 96LEDs/meter, 48 LEDs warm white + 48 LEDs RGB, 18,1W/meter, separable every 10 LEDs (approx. 13cm), fixed with double-sided 3M adhesive tape, excl. converter, ATTENTION: maximum length per feed point 5m, ATTENTION: not resistant to chemical substances or vapours (e.g. chlorine etc.)



DRAWING



TECHNICAL DETAILS

Bulb type	SMD LED 18,1W PRO METER
Luminous flux [lm]	78/198/52/294
Colour temp. [K]	RGB+3000K
Converter	without converter
Light output	direct
Beam angle [°]	100°
Voltage [V]	24 VDC
Material	copper
Length [mm]	5000
Width [mm]	15
Height [mm]	5,5
IP protection class	IP67
Voltage class	protection cl. III
Net weight [kg]	0,53
EAN-Number	9010506647969
Lifetime [h]	L80 B10 20 000

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.