

## LLLX

757-I2050

LLLX SURFACE MOUNTED CEILING LUMINAIRE made of steel sheet, white, light output direct, UGR <19, with converter, dimmability: not dimmable, IP20



## DRAWING

## TECHNICAL DETAILS

|                       |                  |
|-----------------------|------------------|
| System perform. [W]   | 37               |
| Bulb type             | LED              |
| Luminous flux [lm]    | 4000             |
| Colour temp. [K]      | 3000K            |
| CRI                   | >80              |
| UGR                   | <19              |
| Converter             | with converter   |
| Dimming               | not dimmable     |
| Light output          | direct           |
| Voltage [V]           | 220-240V 50/60Hz |
| Material              | steel sheet      |
| Length [mm]           | 1258             |
| Width [mm]            | 264              |
| Height [mm]           | 60               |
| IP protection class   | IP20             |
| Voltage class         | protection cl. I |
| Net weight [kg]       | 1,00             |
| Colour lamp           | white            |
| EAN-Number            | 8596099056995    |
| Energy efficiency cl. | D                |

## LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.